



VACUUM MACHINES



KNZE

KAZE perfectly balances ease-ofuse, sturdy construction and advanced technology. Simple control panel with graphic display. Seamless welding design. Precise vacuum settings with sensor pressure control. Comprehensive maintenance menu. Service Alarm.

Liquid control* INCLUDED with all KAZE machines, in addition to:

- 3-program memory
- Sensor control**
- Soft air
- Double seal
- · Red meat packaging
- Pump cleaning cycle

Optional add-ons:

- Cut-off/wide seal (0.3")
- External vacuum adapter



	KAZE14	KAZE16	KAZE16XL	KAZE16XLD
Power	120V, 960W, 8A, 5-15P	120V, 1600W, 17A, 5-15P	120V, 1760W, 17A, 5-20P	120V, 1760W, 17A, 5-20P
Chamber size (L \times W \times H)	14.6" × 14" × 6"	14.6" × 16.5" × 7"	18" × 16.5" × 7"	16" × 16.5" × 7"
Seal bar	14"	16.5"	16.5"	2 x 16.5"
Pump speed	10 m³h	19 m³h	25 m³h	25 m³h
Machine cycle	35 sec	30 sec	30 sec	30 sec
Dim. (L × W × H)	21.4" x 17.8" × 18"	20.6" x 19.3" × 18.3"	24" x 19.3" × 18.5"	24" x 19.3" × 18.5"
Net weight	79 lbs	126 lbs	150 lbs	159 lbs
Ship dimensions	28.3" × 22.8" × 22.4"	28.3" x 22.8" × 25.6"	28.3" x 22.8" x 25.6"	28.3" x 22.8" × 25.6"
Ship weight	108 lbs	143 lbs	176 lbs	185 lbs

Optional add-ons can be installed at purchase or shipped separately.






Warranty: 1 year parts and labor, 3 years parts (excludes pumps, Teflon seal tape and gaskets)


^{*}Liquid Control: Prevents liquids from boiling during the vacuum process. As soon as the boiling point is detected, the vacuum process stops, and the bag is sealed. With no loss of moisture, the product, pump and vacuum chamber are equally protected.


^{**}Sensor Control: The vacuum process will end as soon the pre-set percentage has been reached.

KAZE14












KAZE16











KAZE16XL














Dimensions expressed in inches